

DS Color Structure Equalizer Spray

Article number 205560 = 150ml

KAO USA Inc.

Linthicum Heights, MD 21090

Created: 06.09.2012, Revision 06.09.2012

Version 01

Page 1 / 7

SECTION 1: Identification of the substance / preparation and of the company

Product identifier **DS Color Structure Equalizer Spray**
Article number 205560 = 150ml

Relevant identified uses of the substance or mixture and uses advised against Treatment

Identified use Cosmetics

Company KAO USA Inc.

Linthicum Heights, MD 21090 / USA
Phone 001410-850-7555

Address enquiries to

Emergency phone Advisory body CHEMTREC: +1 703 527-3887 (24h)

Safety Data Sheet sdb@chemiebuero.de

SECTION 2: Hazards identification

Emergency Overview

Appearance, Odor: liquid, colourless
opaque, characteristic

WARNING
FLAMMABLE LIQUID AND VAPOR
MAY CAUSE EYE IRRITATION.

OSHA Regulatory Status

This product is defined as an Cosmetics. Therefore, this product is exempt from requirements of the hazard communication standard, 29 CFR1910.1200.

Potential health effects

No particular hazards known.

Potential environmental effects

Does not contain any PBT or vPvB substances.

SECTION 3: Composition / Information on ingredients

The product is a mixture.

Range [%]	Substance
40 - <50	Ethanol CAS: 64-17-5
1 - <5	Propan-2-ol CAS: 67-63-0

Comment on component parts

Substances of Very High Concern - SVHC: substances are not contained or are below 0,1%. All chemical substances in this material are included on or exempted from listing on the TSCA Inventory.
For the wording of the listed risk phrases refer to SECTION 16.

SECTION 4: First aid measures

Description of first aid measures	Change soaked clothing.
Inhalation	Ensure supply of fresh air. In the event of symptoms seek for medical treatment.
Skin contact	In case of contact with skin wash off immediately with soap and water. Consult a doctor if skin irritation persists.
Eye contact	In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.
Ingestion	Consult a doctor immediately. Rinse out mouth and give plenty of water to drink. Do not induce vomiting.
Indication of any immediate medical attention and special treatment needed	Treat symptomatically. Forward this sheet to the doctor.

SECTION 5: Fire-fighting measures

Suitable extinguishing media	Alcohol-resistant foam. Dry powder. Carbon dioxide. Water spray jet.
Extinguishing media that must not be used	Full water jet.
Special exposure hazards arising from the substance or preparation itself or combustion products	Unknown risk of formation of toxic pyrolysis products.
Special protective equipment for firefighters	Use self-contained breathing apparatus.
Additional information	Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures	High risk of slipping due to leakage/spillage of product.
Environmental precautions	Keep away from all sources of ignition.
Methods and material for containment and cleaning up	Do not discharge into the drains/surface waters/groundwater. Take up with absorbent material (e.g. general-purpose binder). Dispose of absorbed material in accordance with the regulations.

SECTION 7: Handling and storage

Precautions for safe handling	No special measures necessary if used correctly.
Advice on protection against fire and explosion	Keep away from all sources of ignition - Refrain from smoking.
Requirements for storage rooms and vessels	Keep only in original container.
Advice on storage compatibility	Do not store together with oxidizing agents.
Further information on storage conditions	Keep container tightly closed. Protect from heat/overheating.

DS Color Structure Equalizer Spray

Article number 205560 = 150ml

KAO USA Inc.

Linthicum Heights, MD 21090

Created: 06.09.2012, Revision 06.09.2012

Version 01

Page 3 / 7

SECTION 8: Exposure controls / personal protection**Additional advice on system design** Ensure adequate ventilation on workstation.**Ingredients with occupational exposure limits to be monitored (US)**

Range [%]	Substance
40 - <50	Ethanol
	CAS: 64-17-5, EINECS/ELINCS: 200-578-6, EU-INDEX: 603-002-00-5
	Long-term exposure: 1000 ppm, 1900 mg/m ³ , OSHA, NIOSH
1 - <5	Propan-2-ol
	CAS: 67-63-0, EINECS/ELINCS: 200-661-7, EU-INDEX: 603-117-00-0
	Long-term exposure: 400 ppm, 980 mg/m ³

Respiratory protection

Breathing apparatus in the event of high concentrations.

Hand protection

The details concerned are recommendations. Please contact the glove supplier for further information.

In full contact

butyl rubber, > 120 min (EN 374)

Eye protection

If there is a risk of splashing:

Safety glasses.

Skin protection

None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals.

General protective measures

Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled. The resistance of these equipments to chemicals should be ascertained with the respective supplier.

Avoid contact with eyes.

Do not inhale vapours.

Hygiene measures

Do not eat, drink, smoke or take drugs at work.

Wash hands before breaks and after work.

Delimitation and monitoring of the environmental exposition

See SECTION 6+7.

SECTION 9: Physical and chemical properties

Form	liquid
Color	colourless
	opaque
Odor	characteristic
pH-value	4,0 - 5,0
pH-value [1%]	not determined
Boiling point [°C]	not determined
Flash point [°C]	24 / 75 °F
Flammability [°C]	not determined
Lower explosion limit	not determined
Upper explosion limit	not determined
Oxidizing properties	no
Vapour pressure/gas pressure [kPa]	not determined
Density [g/ml]	0,9263 - 0,9303 (20 °C / 68,0 °F)
Bulk density [kg/m³]	not applicable
Solubility in water	miscible
Partition coefficient [n-octanol/water]	not determined
Viscosity	not determined
Relative vapour density determined in air	not determined
Evaporation speed	not determined
Melting point [°C]	not determined
Autoignition temperature [°C]	not applicable
Decomposition temperature	not determined

DS Color Structure Equalizer Spray

Article number 205560 = 150ml

KAO USA Inc.

Linthicum Heights, MD 21090

Created: 06.09.2012, Revision 06.09.2012

Version 01

Page 4 / 7

SECTION 10: Stability and reactivity

Reactivity	No dangerous reactions known if used as directed.
Chemical stability	The product is stable under standard conditions.
Possibility of hazardous reactions	Reactions with strong oxidizing agents. Evolution of flammable mixtures possible in air when heated above flash point and/or during spraying or misting.
Conditions to avoid	See SECTION 7.2. Strong heating.
Incompatible materials	not determined
Hazardous decomposition products	No hazardous decomposition products known.

SECTION 11: Toxicological information**Information on toxicological effects****Acute toxicity**

Range [%]	Substance
40 - <50	Ethanol, CAS: 64-17-5
	LC50, inhalative, Rat: 124,7 mg/l/4h (IUCLID).
	LD50, oral, Rat: 6200 mg/kg (IUCLID).
	LC50, inhalative, Rat: 95,6 mg/l/4h (RTECS).
1 - <5	Propan-2-ol, CAS: 67-63-0
	LD50, dermal, Rat: 12800 mg/kg bw (IUCLID).
	LD50, oral, Rat: 4396 mg/kg bw (IUCLID).
	LC50, inhalative, Rat: 29 mg/L (8h)(IUCLID).

Acute oral toxicity	not determined
Acute dermal toxicity	not determined
Serious eye damage/irritation	not determined
Skin corrosion/irritation	Non-irritant.
Respiratory or skin sensitisation	not determined
Specific target organ toxicity — single exposure	not determined
Specific target organ toxicity — repeated exposure	not determined
Mutagenicity	not determined
Reproduction toxicity	not determined
Carcinogenicity	not determined

General remarks

The toxicological data are those of the pure product.

The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

This is a cosmetic product that is safe under intended and reasonable foreseeable use. Taking into account the use instructions, the toxicological profile of the ingredients and the evaluation of the final formulation this product is considered as safe and thus not harming human health.

SECTION 12: Ecological information

Toxicity






Range [%]	Substance
40 - <50	Ethanol, CAS: 64-17-5
	LC50, (48h), Leuciscus idus: 8140 mg/l (IUCLID).
	EC50, (48h), Daphnia magna: 9268-14221 mg/l (IUCLID).
1 - <5	Propan-2-ol, CAS: 67-63-0
	EC50, (72h), Scenedesmus subspicatus: >1000 mg/L (IUCLID).
	LC50, (96h), Pimephales promelas: 9640 mg/L (IUCLID).
	EC50, (48h), Daphnia magna: 13299 mg/L (IUCLID).

Fish toxicity	not determined
Daphnia toxicity	not determined
Behaviour in environment compartments	not determined
Behaviour in sewage plant	not determined
Bacteria toxicity	not determined
Biological degradability	not determined
COD	not determined
BOD 5	not determined
AOX-advice	not applicable
2006/11/EC:	not applicable
Other adverse effects	No classification on the basis of the calculation procedure of the preparation directive. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SECTION 13: Disposal considerations

Product	For recycling, consult manufacturer.
Contaminated packaging	Disposal in an incineration plant in accordance with the regulations of the local authorities. Uncontaminated packaging may be taken for recycling.
RCRA Hazard Class (40CFR 261)	Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities.

SECTION 14: Transport information

Transport by land according to ADR/RID	UN 1993 Flammable liquid, n.o.s. (Ethanol, Isopropanol) 3 III
- Classification Code	F1
- Label	
- ADR LQ	5 I
- ADR 1.1.3.6 (8.6)	Transport category (tunnel restriction code) 3 (D/E)
Inland navigation (ADN)	UN 1993 Flammable liquid, n.o.s. (Ethanol, Isopropanol) 3 III
- Classification Code	F1
- Label	
Marine transport in accordance with IMDG	UN 1993 Flammable liquid, n.o.s. (Ethanol, Isopropanol) 3 III
- EMS	F-E, S-E
- Label	
- IMDG LQ	5 I
Air transport in accordance with IATA	UN 1993 Flammable liquid, n.o.s. (Ethanol, Isopropanol-mixture) 3 III
- Label	
DOT Road Shipment Information (49 CFR)	UN/NA 1993 Flammable liquid, n.o.s. (Ethanol, Isopropanol) 3 III
- Label	

SECTION 15: Regulatory information

US Regulations

National regulations	29 CFR 1910.1200, ANSI Z400.1-2010, OSHA-PEL, ACGIH-TLV, NTP, IARC, SARA Title III, NFPA, TSCA, California - Prop. 65
- SARA, 302	This product is not classified as hazardous under SARA 302.
- SARA, 311	This product is not classified as hazardous under SARA 311.
- SARA, 313	One or some ingredient(s) are listed under this regulation.
- CA Proposition 65	All chemical substances in this material are not named in California-P65 list.
- TSCA	All chemical substances in this material are included on or exempted from listing on the TSCA Inventory.
- FDA	not determined
American Conference of Governmental Industrial Hygienists - ACGIH	Ingredients not listed as carcinogens.
International Agency for Research on Cancer IARC	Ingredients not listed as carcinogens.
National Toxicology Program - NTP	This product is named NTP - National Toxicology Program.
Transport-regulations	DOT-Classification, ADR (2011); IMDG-Code (2011, 35. Amdt.); IATA-DGR (2012).

EC Regulations

	1967/548 (1999/45); 1991/689 (2001/118); 1999/13; 2004/42; 648/2004; 1907/2006 (Reach); 1272/2008; 75/324/EEC (2008/47/EC); 453/2010/EC
Labelling	The product is classified and required to be labelled in accordance with EC-Directives
Hazard symbols	none
R-phrases	R 10: Flammable.
S-phrases	S 25: Avoid contact with eyes.
Special labelling	none

DS Color Structure Equalizer Spray

Article number 205560 = 150ml

KAO USA Inc.

Linthicum Heights, MD 21090

Created: 06.09.2012, Revision 06.09.2012

Version 01

Page 7 / 7

SECTION 16: Other informations

Observe employment restrictions for people yes

648/2004/CE

not applicable

HMIS Ratings

HEALTH	2	2 - Moderate Hazard
FLAMMABILITY	3	3 - Severe Hazard
REACTIVITY	0	0 - Minimal Hazard
PERSONAL PROTECTION	B	B - Safety Glasses and Gloves

NFPA Ratings

3	TOP, FLAMMABILITY: 3 - Severe Hazard
2 0	LEFT, HEALTH: 2 - Moderate Hazard RIGHT, REACTIVITY: 0 - Minimal Hazard
FLL	BOTTOM, SPECIAL NOTICE: FLL - Flammable Liquid

Modified position

none

Key / Legende:

ACGIH = American Conference of Governmental Industrial Hygienists; CAS = Chemical Abstracts Service; CERCLA = Comprehensive Environmental Response, Compensation, and Liability Act; CFR = Code of Federal Regulations; CPR = Controlled Products Regulations; DOT = Department of Transportation; EINCES = European Inventory of Existing Commercial Chemical Substances; EPA = Environmental Protection Agency; IARC = International Agency for Research on Cancer; IATA = International Air Transport Association; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; SARA = Superfund Amendments and Reauthorization Act; STEL = Short Term Exposure Limit; TSCA = Toxic Substances Control Act

Copyright: Chemiebüro®